

WR 3000MER

Product no.: T0053368899N



Benefits

- › Power unit, 3 channels with soldering iron WP 120, desoldering iron DSX 120 and hot air iron HAP 200
- › Large allround set for all repair jobs
- › Desoldering iron DSX 120 for horizontal applications




For this purpose, we recommend:



Solder fume extractors



Pre-heating plates



Zubehoer



Soldering tips



Technical Data

| | |
|--|--|
| Dimensions L x W x H (mm) | 280 x 240 x 103 |
| Dimensions L x W x H (inches) | 11,02 x 9,45 x 4,06 |
| Weight (approx.) in kg | 7.3 |
| Voltage | 230 V |
| Power | 400 W |
| Channels | 3 |
| Temperature range (depends on tool) °C | 50 - 550 |
| Temperature range (depends on tool) °F | 150 - 950 |
| Temperature accuracy °C | ±9 |
| Temperature accuracy °F | ±17 |
| Temperature accuracy for hot air °C | tbd |
| Temperature accuracy for hot air °F | tbd |
| Temperature stability °C | ±2 |
| Temperature stability °F | ±4 |
| Equipotential bonding socket | Via a 3.5 mm jack bush (initial state-hard-grounded) |
| Display | LCD |
| Additional vacuum pump | Pick Up |
| Max. hot air flow rate l/min (depends on tool) | 15 |
| Capacity l/min | 18 |
| Max. vacuum | --- |
| Interface | --- |

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE