



2.92mm Male to 2.92mm Male Cable RG405 Type .086 Coax

Electrical Specifications

Description	Min Typ		Max	Units	
Frequency Range	DC		40	GHz	
VSWR			1.35:1		

Copper Clad Steel, Silver

PTFE

Mechanical Specifications

Cable Assembly

Diameter 0.312 in [7.92 mm]

Cable

Cable Type RG-405AL Impedance 50 Ohms Inner Conductor Type Solid

Inner Conductor Material and Plating

Dielectric Type Number of Shields

Shield Layer 1 Tinned Aluminum

Connectors

Description	Connector 1	Connector 2		
Туре	2.92mm Male	2.92mm Male		
Impedance	50 Ohms	50 Ohms		
Contact Material & Plating	Beryllium Copper, Gold	Beryllium Copper, Gold		
Contact Plating Spec.	50μ in. minimum	50μ in. minimum		
Dielectric Type	PCTFE	PCTFE		
Coupling Nut Material & Plating Passivated Stainless Stee		Passivated Stainless Steel		
Hex Size	5/16 in.	5/16 in.		
Torque	8 in-lbs [0.9 Nm]	8 in-lbs [0.9 Nm]		
Body Material & Plating	Beryllium Copper, Gold	Beryllium Copper, Gold		
Body Plating Spec.	50μ in. minimum	50µ in. minimum		

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

Plotted and Other Data

Notes:



Configuration:

- 2.92mm Male
- 2.92mm Male
- RG-405AL

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com


sales@fairviewmicrowave.com





- Length

Typical Performance Data



2.92mm Male to 2.92mm Male Cable RG405 Type .086 Coax from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: 2.92mm Male to 2.92mm Male Cable RG405 Type .086 Coax FMC2929986


URL: http://www.fairviewmicrowave.com/2.92mm-male-2.92mm-male-cable-rg-405al-coax-fmc2929986-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

FMC2929986-12 = 12 inches long cable FMC2929986-100cm = 100 cm long cable







FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
2.92mm Male to 2.92mm Male Cable RG405 Type .086 Coax	DWG NO FMC2929986			CAGE CODE 3FKR5		
	CAD FILE 042115	SHEET	SCALI	E N/A	SIZE A	2233