

Magnetic Rope Detector HRD-100 Steel Rope Ultrasonic Flaw Detector

	Product Details:		
	Place of Origin:	China	
	Brand Name:	HUATEC	
	Certification:	CE	
	Model Number:	HRD-100	
	Payment & Shipp	ing Terms:	
	Minimum Order Q	uantity: 1 set	
	Packaging Details	: Carton	
	Delivery Time:	7 days	
Large Image : <u>Magnetic Rope Detector</u> <u>HRD-100 Steel Rope Ultrasonic Flaw</u> <u>Detector</u>	Payment Terms:	TT /LC	
	Supply Ability:	200 sets per month	

Chat Now

Detailed Product Description

Mining rope detector, steel rope flaw detector

Specification

- For inspection of ropes with diameter from 1 to 300 mm (0.04" to 11.8")
- Size 330 x 235 x 190 mm (13" x 9, 3" x 7, 5 ")
- Weight 15 kg (33 lbs)
- Speed along the rope during inspection from 0 to 6 m/s (0 to 6, 54 yards/s) **Features**
- Dual-function: LMA and LF capability
- Speed does not affect readings
- Accurate distance wheel assembly
- Easy to install and re-install
- Easy to handle and fix on the rope
- 3 changeable hall sensor units
- Temperature range -10 +50°C
- PC software control directly, continuously testing rope length more than 10000m
- Power: AC 220V±10%

China Good Quality Ultrasonic Flaw Detector Supplier. Copyright © 2011 - 2017 huatecgroup.com. All Rights Reserved.



- Working temperature: $-20^{\circ}C \sim 40^{\circ}C$
- Storage temperature: -40°C~60°C
- Relative humidity:≤90%RH

Typical applications but not limited with:

Inspection of mining ropes, aerial ropeways (mostly ropes of chairlifts and gondola lifts), guy (suspension) ropes of bridges.

Standard accessories

Probe	1 set	Real time alarm	1pc
Signal cable	1pc	HRD PC analyse software	1set
laptop	1pc	Communication cable	1pc
Charger	1pc	Tool	1set
Instruction manual	1set		