Crimping Tool　For Non-Insulated Terminals　Parallel type

TP-8P Capacity IEC/DIN:1.5/2.5/6/10㎟　AWG:16/14/10/8　JIS:1.25/2/5.5/8㎟ JISParallel type

JIS C 9711
JQ0314008

- All dice are in parallel.
- Crimping different size terminals without re-holding handles.

MADE IN JAPAN

CRIMPING TOOL

For Non-Insulated Terminals: TP-2 TP-8 TP-8P TP-14 TP-5 TP-5M TP-5S TP-3

For E-Type Sleeve Terminals: TP-R

SAFE & SECURE! SPEEDY CRIMPING

JIS JQA
JIS C 9711
JQ0314008

ALL TESTS PASSED

Continuous durability test 30,000 times · Tensile test · Salt water spraying · Heat aging · Electrical resistance · Vibration fatigue

Temporary holding function

Cables can be inserted smoothly into terminals due to the deformless temporary holding function.



Tsunoda

*Temporary holding function is not loaded on TP-2

Both side colored size marks

Colored size marks help you to check the size of crimping die even in the room where is unsufficiently lighted and improve your work efficiency.



Toggle mechanism

Reducing required loads for each stroke of gear.

Crimp completion checking function

Handles don't open until crimping done.

Clear crimped mark!

Molded elastomer resin cover

Soft texture elastomer grip reduces fatigue of Continuous crimping works.

Crimping Tool Usable Terminals

Terminal (㎟)	0.3	0.5	1.25	2.0	3.5	5.5	8.0	14.0	22.0	38.0
TP-2 (JIS)			○	○						
TP-3		○	○	○	○					
TP-5 (JIS)			○	○		○				
TP-5S	○		○	○	○					
TP-5M			○	○	○	○				
TP-8 (JIS)			○	○		○	○			
TP-8P (JIS)			○	○		○	○			
TP-14 (JIS)			○	○		○	○	○		
TP-22 (JIS)						○	○	○	○	
TP-38 (JIS)							○	○	○	○
TP-R (JIS)	E-L・E-M・E-S									

Specifications

- Material | Alloy steel
- Head hardness [HRC] | 42～48
- Handle part hardness [HRC] | 43～47
- Handle cover | Elastomeric molded resin grips



	Size[mm]				Weight [g]	EAN-code (4952269)
	Overall length	Head width	Head thickness	Handle width		
TP-8P	251	48	6	74	420	113358

Terminal Size			
JIS standard ㎟	IEC・DIN standard ㎟	American Wire Gauge	Crimped Mark
1.25	1.5	16	1
2	2.5	14	2
5.5	6	10	5
8	10	8	8