

Automatic Side-Seal Stainless Steel Strapping Machine

The RQ7000M is the ideal machine for moisture-laden environments like meat, poultry and seafood processing. It boasts the advanced high-speed sealing head and most of the advanced features of Strapack Automatic models such as self-loading, refeed and loop ejection.

- **Fast!**
The RQ7000M is capable of up to 50 straps per minute (1.2 seconds per strap).
- **Built to Last**
Permanently lubricated mechanisms, side-seal design and body parts made of stainless steel and other water proof parts make the RQ7000M the ideal machine for moist environments. The bottom of the cabinet is reinforced to provide extra protection where moisture exposure is greatest. The cabinet is fully enclosed to protect the components from saltwater runoff, oil and dust.
- **Adjustable Table Height**
The roller table height is adjustable to three positions; 624mm, 642mm (standard), 664mm and it can be removed to fit the RQ7000M into existing conveyor system.
- **Tandem Type is available**
The double-strapping head configuration allows packages to be simultaneously strapped. The minimum distance between the two straps is 380mm.



RQ7000M

Standard Specifications (Arch size 700 mm wide x 650 mm high)

Dimension	Width	1580 mm
	Height	1772 mm
	Depth	642 mm
	Weight	220 kg
Package Size	Max	W 680 X H 500 mm
	Min	W 30 X H 80 mm
Joint / Strap		heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm
Strap Tension		690 N (70 kgf) / 392 N (40 kgf) *CE Spec.
Power Supply		380, 400, 415V Three phase 50/60Hz 0.69kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2020 Strapack Corporation

DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone 81-3-6278-1806 Fax. 81-3-6278-1807
(URL) <http://www.strapack.com> (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone: 1-510-475-6000 Fax: 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone: 32-3-355-1520 Fax: 32-3-355-1521